

Fanless System

Slim Type for IBASE MI953AF Mini-ITX Motherboard

Fanless System

Slim Type for IBASE MI945 Mini-ITX Motherboard



Features

- Onboard Intel® Core™ i7-620M / i5-520M processor Mini-ITX system w/ IBASE MI953AF Mini-ITX motherboard
- Chassis with Intel® Core™ processors
- Available in silver color
- One 2.5" HDD drive bay
- Fanless operation
- Wall mount kit included

Specifications

System Mainboard	MI953AF
Construction	Aluminum
Chassis Color	Silver
Front Panel External I/O	Power LED, HDD LED, Reset button, Power on/off button, 2x USB 2.0 ports
Rear Panel External I/O	2x DVI, 1x VGA+COM, 2x dual USB+RJ45, 1x dual USB + mini DIN KB/MS x1, 1x audio port (3-port), DC-in jack
Storage	1x 2.5" HDD 40GB, industrial-grade
Power Supply	80W power adaptor
Mounting	Desktop or wall mount kit (wall mount kit included)
Dimensions	199mm(W) x 232mm(D) x 63.4mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

AMI200-953AF-i7	Aluminum System with MI953AF, Intel® Core™ i7-620M(2.66GHz) CPU, 4GB DDR3 SO-DIMM 2.5" 40GB HDD(Industrial-grade), 80W power adaptor
AMI200-953AF-i5	Aluminum System with MI953AF, Intel® Core™ i5-520M(2.4GHz) CPU, 4GB DDR3 SO-DIMM 2.5" 40GB HDD(Industrial-grade), 80W power adaptor

Features

- Mini-ITX system with IBASE MI945 Mini-ITX motherboard
- Chassis with Intel® Core™2 Duo T9400 processor, 2.53GHz
- Available in silver color
- One 2.5" HDD drive bay
- Fanless operation
- Wall mount kit included

Specifications

System Mainboard	MI945F/ MI945AF
Construction	Aluminum
Chassis Color	Silver
Front Panel External I/O	Power LED, HDD LED, Reset button, Power on/off button, 2x USB 2.0 ports
Rear Panel External I/O	Audio, 2x LAN, 4x USB, COM, VGA, KB/MS
Storage	1x 2.5" 160GB HDD
Power Supply	80W power adaptor
Mounting	Desktop or wall mount (wall mount kit included)
Dimensions	199mm(W) x 232mm(D) x 63.4mm(H)
Operating Temperature	0°C~ 45°C (32°F~113°F)
Storage Temperature	-20°C~80°C (-4°F~176°F)
Relative Humidity	5 ~ 90% @ 45°C, non-condensing
Vibration	CFD: 5 grms/5~500Hz random operation HDD: 1g/5~500Hz random operation

Ordering Information

AMI200-945F-D1	Aluminum System with MI945F, Intel® T9400 (2.53GHz) CPU, 4GB DDR2 SO-DIMM, 2.5" 160GB HDD, ID450 converter, ID392 DVI Board, 80W power adaptor
AMI200-945AF-D1	Aluminum System with MI945AF, Intel® T9400 (2.53GHz) CPU, 4GB DDR2 SO-DIMM, 2.5" 160GB HDD, ID450 converter, ID392 DVI Board, 80W power adaptor, iAMT 4.0

- 1 eFlex Platform
- 2 Motherboards
- 3 Disk-Size SBCs
- 4 CPU Modules
- 5 PC/104 Plus
- 6 CPU Cards
- 7 Embedded Systems
- 8 Network Security Appliance